NSN 5306-00-559-5267

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-559-5267

Thread Class:3aThread Direction:Right-handThread Length:Between 1.250 inches and 1.440 inchesFastener Length:Between 3.485 inches and 3.515 inchesHead Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesFinished headThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFreatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseThread Series Designator:UncShelf Life:
Thread Direction: Right-hand Thread Length: Between 1.250 inches and 1.440 inches Fastener Length: Between 3.485 inches and 3.515 inches Head Style: Double hexagon extended washer Head Height: 0.500 inches Width Between Flats: Between 0.495 inches and 0.503 inches Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Diameter: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Right-handRight-handThread Length:Between 1.250 inches and 1.440 inchesFastener Length:Between 3.485 inches and 3.515 inchesHead Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseThread Series Designator:Unc
Tread Length:Between 1.250 inches and 1.440 inchesFastener Length:Between 3.485 inches and 3.515 inchesHead Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseUnc
Between 1.250 inches and 1.440 inches Fastener Length: Between 3.485 inches and 3.515 inches Head Style: Double hexagon extended washer Head Height: 0.500 inches Width Between Flats: Between 0.495 inches and 0.503 inches Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Fatures Provided: Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Fastener Length:Between 3.485 inches and 3.515 inchesHead Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesBetween 2.045 inches and 2.265 inchesFried Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseThread Series Designator:Unc
Between 3.485 inches and 3.515 inchesHead Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseUnc
Head Style:Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseUnc
Double hexagon extended washerHead Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseUnc
Head Height:0.500 inchesWidth Between Flats:Between 0.495 inches and 0.503 inchesExtended Washer Diameter:Between 0.735 inches and 0.750 inchesExtended Washer Thickness:0.178 inches0.178 inchesThread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseUnc
0.500 inches Width Between Flats: Between 0.495 inches and 0.503 inches Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Width Between Flats: Between 0.495 inches and 0.503 inches Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.178 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Between 0.495 inches and 0.503 inches Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Extended Washer Diameter: Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Between 0.735 inches and 0.750 inches Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Extended Washer Thickness: 0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
0.178 inches Thread Diameter: 0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Thread Diameter:0.500 inchesGrip Length:Between 2.045 inches and 2.265 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Material:SteelMaterial Specification:Sae gr 8 assn standard single material responseThread Series Designator:Unc
0.500 inches Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Grip Length: Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Between 2.045 inches and 2.265 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Finished head Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Thready Qty Per Inch (tpi): 13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
13 Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Material: Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Steel Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Material Specification: Sae gr 8 assn standard single material response Thread Series Designator: Unc
Sae gr 8 assn standard single material response Thread Series Designator: Unc
Thread Series Designator: Unc
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0