## NSN 5306-00-565-6108

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-565-6108 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.180 inches and 1.200 inches **Fastener Length:** Between 5.330 inches and 5.350 inches **Head Style:** Dee chamfer **Head Diameter:** Between 0.980 inches and 1.000 inches **Head Height:** 0.600 inches **Distance From Centerline To Flat:** Between 0.415 inches and 0.419 inches First Diameter From Head: Between 0.550 inches and 0.635 inches **Second Diameter From Head:** Between 0.541 inches and 0.545 inches **Third Diameter From Head:** Between 0.624 inches and 0.625 inches **Fourth Diameter From Head:** Between 0.541 inches and 0.545 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.370 inches and 0.390 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.170 inches and 2.190 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 3.050 inches and 3.070 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Between 3.760 inches and 3.780 inches **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): **Askewed Head Angle:** 40.0 degrees **Externally Relieved Body Diameter Quantity:** 

4

Material:

Steel

## NSN 5306-00-565-6108

Externally Relieved Body Bolt - Page 2 of 2



Materiai	Specif	icatio	n:

31001-05, fscm 15434 mfr ref single material response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0