NSN 5306-00-568-0272

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-568-0272

-						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.440 inches and 0.560 inches						
Fastener Length:						
1.750 inches						
Head Style:						
Hexagon						
Head Height:						
0.190 inches						
Width Between Flats:						
Between 0.490 inches and 0.502 inches						
Shank Unthreaded Hole Diameter:						
0.076 inches first hole						
Thread Diameter:						
0.312 inches						
Features Provided:						
Finished head						
Thready Qty Per Inch (tpi):						
24						
Hardness Rating:						
32.0 rockwell c and 36.0 rockwell c						
Distance From Head Largest Bearing Surface To Shank Hole Center:						
1.620 inches first hole						
Surface Finish:						
50.0 microinches bearing surface of head						
Special Features:						
Special Features: Undercut to 0.280 in. Dia						
Undercut to 0.280 in. Dia						
Undercut to 0.280 in. Dia Material:						
Undercut to 0.280 in. Dia Material: Steel comp 8740						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification:						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment:						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification:						
Undercut to 0.280 in. Dia Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response						

N/a

NSN 5306-00-568-0272Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0