

View Online at <https://aerobasegroup.com/nsn/5306-00-568-5146>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.532 inches and 0.609 inches

Fastener Length:

Between 3.516 inches and 3.562 inches

Head Style:

Hexagon

Head Height:

Between 0.176 inches and 0.186 inches

Width Between Flats:

0.438 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 2.953 inches and 2.984 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Bfg 305, type 1, class c, fscm 83187 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.