NSN 5306-00-574-0368

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-574-0368 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.594 inches and 0.644 inches **Fastener Length:** Between 1.354 inches and 1.384 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Hole Diameter:** 0.055 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole Material: Steel

Surface Treatment:

Cadmium

NSN 5306-00-574-0368

Shear Bolt - Page 2 of 2



Surface Treatm	ent Specification:
----------------	--------------------

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas626 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0