NSN 5306-00-576-6364

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-576-6364 **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.760 inches Fastener Length: Between 2.052 inches and 2.072 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.348 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches First Diameter From Head: Between 0.218 inches and 0.228 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches **Thread Diameter:** 0.250 inches **Nonstandard Thread Pitch Diameter:** +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 601 **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-00-576-6364

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0