

View Online at <https://aerobasegroup.com/nsn/5306-00-576-6486>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.550 inches

**Fastener Length:**

3.090 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

0.625 inches

**Shank Unthreaded Hole Diameter:**

0.108 inches first hole

**First Diameter From Head:**

0.438 inches

**Second Diameter From Head:**

0.342 inches

**Third Diameter From Head:**

0.438 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.141 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.297 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

2.540 inches

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.920 inches first hole

**Externally Relieved Body Diameter Quantity:**

3

**Special Features:**

Cotterpin holes 90.0 degrees apart

**Material:**

Steel comp 2330

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0