NSN 5306-00-576-7739

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-576-7739

Thread Direction: Right-hand Thread Length: 0.469 inches Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches Grip Length:
Thread Direction: Right-hand Thread Length: 0.469 inches Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Right-hand Thread Length: 0.469 inches Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Thread Length: 0.469 inches Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
0.469 inches Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Fastener Length: 3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
3.781 inches Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Head Style: Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Hexagon Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Head Height: Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Between 0.428 inches and 0.440 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches
0.046 inches Thread Diameter: 0.250 inches
Thread Diameter: 0.250 inches
0.250 inches
Grip Length:
3.312 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140
Material Specification:
Mil-b-6812 military specification all material responses
Surface Treatment:
Cadmium and chromate

Qq-p-416, ty2, class 3 federal specification single treatment response

Surface Treatment Specification:

NSN 5306-00-576-7739

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-b-6812 spec.