

View Online at <https://aerobasegroup.com/nsn/5306-00-579-0680>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.749 inches and 0.828 inches

**Fastener Length:**

Between 2.203 inches and 2.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.265 inches and 0.297 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.422 inches and 1.454 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.031 inches first hole and 2.063 inches first hole

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-b-6812 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.