

View Online at <https://aerobasegroup.com/nsn/5306-00-579-0710>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.740 inches and 0.820 inches

Fastener Length:

Between 2.490 inches and 2.510 inches

Head Style:

Hexagon

Head Height:

Between 0.209 inches and 0.229 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Shank Unthreaded Hole Diameter:

0.094 inches first hole and 0.101 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 1.690 inches and 1.750 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.350 inches first hole and 2.370 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0