NSN 5306-00-579-1746

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-579-1746

Thread Direction: Right-hand Thread Length: 1.500 inches Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life: N/a	Thread Class:
Thread Direction: Right-hand Thread Length: 1.500 inches Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Right-hand Thread Length: 1.500 inches Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Thread Length: 1.500 inches Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Fastener Length: 4.000 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	-
Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	•
Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	-
Width Between Flats: Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	-
Between 0.906 inches and 0.938 inches Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
Thread Diameter: 0.625 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Width Between Flats:
Consider the second of the sec	Between 0.906 inches and 0.938 inches
Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Thread Diameter:
Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	0.625 inches
Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Features Provided:
Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Finished head
Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Thready Qty Per Inch (tpi):
55000 pounds per square inch Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	11
Hardness Rating: 95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Min. Tensile Strength (psi):
95.0 rockwell b Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	55000 pounds per square inch
Material: Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Hardness Rating:
Steel Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	95.0 rockwell b
Material Specification: Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Material:
Sae gr 1 assn standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Steel
Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Material Specification:
Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Sae gr 1 assn standard single material response
Surface Treatment Specification: Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Surface Treatment:
Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Zinc
Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Surface Treatment Specification:
Thread Series Designator: Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	Qq-z-325, type 2, cl 2 or 3 federal specification single treatment response
Unc Specification Or Standard: 2 type and 1 grade Shelf Life:	
2 type and 1 grade Shelf Life:	
2 type and 1 grade Shelf Life:	Specification Or Standard:
Shelf Life:	
· · · · ·	
Unit Of Measure:	
Demilitarization:	

No

NSN 5306-00-579-1746Machine Bolt - Page 2 of 2



Fiig:

A003b0