NSN 5306-00-579-1948

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-579-1948 **Thread Direction:** Right-hand Thread Length: Between 0.885 inches and 0.925 inches Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.276 inches and 0.286 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.190 inches and 0.250 inches **Thread Diameter:** 0.312 inches **Nonstandard Thread Pitch Diameter:** +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 601 **Material Specification:** Ams 6304 assn standard single material response **Surface Treatment:** Nickel and cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-00-579-1948

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0