

View Online at <https://aerobasegroup.com/nsn/5306-00-579-3302>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.311 inches and 0.378 inches

Fastener Length:

Between 2.290 inches and 2.310 inches

Head Style:

Dished hexagon

Head Height:

Between 0.157 inches and 0.172 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.812 inches and 1.828 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

7510 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.917 inches first hole and 1.943 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0