

View Online at <https://aerobasegroup.com/nsn/5306-00-579-5406>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.844 inches and 0.906 inches

**Fastener Length:**

Between 1.719 inches and 1.871 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.750 inches

**Head Height:**

Between 0.229 inches and 0.239 inches

**Shoulder Diameter:**

0.526 inches first shoulder and 0.531 inches first shoulder

**Shoulder Length:**

0.552 inches first shoulder and 0.562 inches first shoulder

**Rib Major Diameter:**

Between 0.552 inches and 0.562 inches

**Rib Length:**

Between 0.552 inches and 0.562 inches

**Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:**

0.062 inches

**Thread Diameter:**

0.500 inches

**Features Provided:**

Casehardened

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

110000 pounds per square inch

**Hardness Rating:**

20.0 rockwell c and 24.0 rockwell c

**Shoulder Shape:**

Ribbed first shoulder

**Material:**

Steel comp 1020

**Material Specification:**

Qq-s-634 federal specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0