NSN 5306-00-579-5406

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-579-5406

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.844 inches and 0.906 inches
Fastener Length:
Between 1.719 inches and 1.871 inches
Head Style:
Pan no. 2
Head Diameter:
0.750 inches
Head Height:
Between 0.229 inches and 0.239 inches
Shoulder Diameter:
0.526 inches first shoulder and 0.531 inches first shoulder
Shoulder Length:
0.552 inches first shoulder and 0.562 inches first shoulder
Rib Major Diameter:
Between 0.552 inches and 0.562 inches
Rib Length:
Between 0.552 inches and 0.562 inches
Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:
0.062 inches
Thread Diameter:
0.500 inches
Features Provided:
Casehardened
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
110000 pounds per square inch
Hardness Rating:
20.0 rockwell c and 24.0 rockwell c
Shoulder Shape:
Ribbed first shoulder
Material:
Steel comp 1020
Material Specification:
Qq-s-634 federal specification single material response
Surface Treatment:

Cadmium

NSN 5306-00-579-5406

Ribbed Shoulder Bolt - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0