

View Online at <https://aerobasegroup.com/nsn/5306-00-580-9702>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.365 inches and 0.465 inches

**Fastener Length:**

1.740 inches

**Head Style:**

Hexagon

**Head Height:**

0.200 inches

**Width Between Flats:**

0.688 inches

**First Diameter From Head:**

Between 0.354 inches and 0.359 inches

**Second Diameter From Head:**

Between 0.431 inches and 0.436 inches

**Third Diameter From Head:**

0.310 inches

**Fourth Diameter From Head:**

Between 0.431 inches and 0.436 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.100 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.220 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.155 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

1.275 inches

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-225/6 t351 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 1a military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.