NSN 5306-00-580-9934



Externally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-580-9934 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.035 inches and 1.082 inches **Fastener Length:** Between 1.265 inches and 1.312 inches **Head Style:** Hexagon **Head Height:** 0.219 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Hole Diameter:** 0.070 inches First Diameter From Head: Between 0.190 inches and 0.210 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.230 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Hexagon corners **Externally Relieved Body Diameter Quantity:** 1 Material: **Material Specification:** Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military

Steel

specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single material response or ams 6300 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

NSN 5306-00-580-9934

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-5626 spec.