Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-580-9934

3a Thread Direction:	
Thread Direction:	
Right-hand	
Thread Length:	
Between 1.035 inches and 1.082 inches	
Fastener Length:	
Between 1.265 inches and 1.312 inches	
Head Style:	
Hexagon	
Head Height:	
0.219 inches	
Width Between Flats:	
Between 0.428 inches and 0.440 inches	
Hole Diameter:	
0.070 inches	
First Diameter From Head:	
Between 0.190 inches and 0.210 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
0.230 inches	
Thread Diameter:	
0.250 inches	
Hole Quantity:	
3	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
28	
Hardness Rating:	
36.0 rockwell c and 40.0 rockwell c	
Hole Configuration Style:	
Hexagon corners	
Externally Relieved Body Diameter Quantity:	
1	
Material:	
Steel	
Material Specification:	
Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-605) military
specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification	on single
material response or ams 6300 assn standard single material response	
Surface Treatment:	
Cadmium	

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.