

View Online at <https://aerobasegroup.com/nsn/5306-00-582-6199>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.453 inches

**Fastener Length:**

Between 0.890 inches and 0.937 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.365 inches and 0.377 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.484 inches and 0.516 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.750 inches first hole and 0.782 inches first hole

**Material:**

Steel comp 321 or steel comp 347

**Material Specification:**

Ams 5645 assn standard 1st material response or ams 5646 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas501 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0