## NSN 5306-00-582-6705

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-6705

Thre	ad Class:
3a	
Thre	ad Direction:
Righ	t-hand
Thre	ad Length:
0.64	0 inches
Fast	ener Length:
1.57	8 inches
Head	d Style:
Hexa	agon
Head	d Height:
Betw	een 0.203 inches and 0.235 inches
Wid	h Between Flats:
Betw	een 0.553 inches and 0.565 inches
Hole	Diameter:
0.07	0 inches
Sha	nk Unthreaded Hole Diameter:
0.10	6 inches first hole
Thre	ad Diameter:
0.37	5 inches
Grip	Length:
0.93	8 inches
Hole	Quantity:
1	
Hole	э Туре:
Drille	ed
Feat	ures Provided:
Finis	hed head
Thre	ady Qty Per Inch (tpi):
24	
Min.	Tensile Strength (psi):
1250	000 pounds per square inch
Hard	Iness Rating:
26.0	rockwell c and 32.0 rockwell c
Hole	Configuration Style:
Hexa	agon flats
Dist	ance From Head Largest Bearing Surface To Shank Hole Center:
1.37	6 inches first hole
Mate	erial:
Stair	nless steel
Mate	erial Specification:
~	-

Qq-s-770 federal specification single material response

## NSN 5306-00-582-6705

Machine Bolt - Page 2 of 2

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

