

View Online at <https://aerobasegroup.com/nsn/5306-00-582-6762>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.440 inches and 0.512 inches

**Fastener Length:**

Between 2.330 inches and 2.370 inches

**Head Style:**

Hexagon

**Head Height:**

0.220 inches

**Width Between Flats:**

Between 0.552 inches and 0.564 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.016 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.796 inches and 1.828 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.150 inches first hole and 2.180 inches first hole

**Material:**

Steel

**Material Specification:**

Mil-s-5626 military specification single material response or mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

E120 fscm 81205 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.