

View Online at <https://aerobasegroup.com/nsn/5306-00-582-6762>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.512 inches

Fastener Length:

Between 2.330 inches and 2.370 inches

Head Style:

Hexagon

Head Height:

0.220 inches

Width Between Flats:

Between 0.552 inches and 0.564 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.016 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 1.796 inches and 1.828 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.150 inches first hole and 2.180 inches first hole

Material:

Steel

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

E120 fscm 81205 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.