## NSN 5306-00-582-6893

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-6893

| Thread Class:   |
|---|
| 3a  |
| Sa<br>Thread Direction:                                 |
|   |
| Right-hand  |
| Thread Length:<br>0.781 inches                          |
|   |
| Fastener Length:<br>1.469 inches                        |
|   |
| Head Style:   |
| Hexagon   |
| Head Height:  |
| Between 0.265 inches and 0.297 inches                   |
| Width Between Flats:                                    |
| Between 0.740 inches and 0.752 inches                   |
| Hole Diameter:  |
| 0.070 inches  |
| Thread Diameter:  |
| 0.500 inches  |
| Grip Length:  |
| 0.688 inches  |
| Hole Quantity:  |
| 1   |
| Hole Type:  |
| Drilled   |
| Features Provided:                                      |
| Finished head   |
| Thready Qty Per Inch (tpi):                             |
| 20  |
| Min. Tensile Strength (psi):                            |
| 125000 pounds per square inch                           |
| Hardness Rating:  |
| 26.0 rockwell c and 32.0 rockwell c                     |
| Hole Configuration Style:                               |
| Hexagon flats   |
| Material:   |
| Stainless steel   |
| Material Specification:                                 |
| Qq-s-770 federal specification single material response |
| Surface Treatment:                                      |
| Passivate   |
| Thread Series Designator:                               |
|   |

Unf

## NSN 5306-00-582-6893

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

