## NSN 5306-00-582-6902

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-6902 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 3.156 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** 2.750 inches **Hole Quantity:** 1 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.016 inches first hole Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf

Shelf Life: N/a

## NSN 5306-00-582-6902

Machine Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.