NSN 5306-00-582-6911

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-6911

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.782 inches
Fastener Length:
1.094 inches
Head Style:
Hexagon
Head Height:
Between 0.265 inches and 0.297 inches
Width Between Flats:
Between 0.740 inches and 0.752 inches
Hole Diameter:
0.070 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole
Thread Diameter:
0.500 inches
Grip Length:
0.312 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.921 inches first hole
Material:
Stainless steel
Material Specification:
Qq-s-770 federal specification single material response

NSN 5306-00-582-6911

Machine Bolt - Page 2 of 2



Surrace	reatment
Passivat	е

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0