

View Online at <https://aerobasegroup.com/nsn/5306-00-582-6935>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.954 inches

Fastener Length:

2.016 inches

Head Style:

Hexagon

Head Height:

Between 0.328 inches and 0.360 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Hole Diameter:

0.070 inches

Thread Diameter:

0.625 inches

Grip Length:

1.062 inches

Hole Quantity:

1

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Hole Configuration Style:

Hexagon flats

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-b-6812 military specification all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.