## NSN 5306-00-582-6982

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-6982

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.782 inches
Fastener Length:
1.844 inches
Head Style:
Hexagon
Head Height:
Between 0.265 inches and 0.297 inches
Width Between Flats:
Between 0.740 inches and 0.752 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.500 inches
Grip Length:
1.062 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140
Material Specification:
Mil-b-6812 military specification all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

## NSN 5306-00-582-6982

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.

