NSN 5306-00-582-8796

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-582-8796

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.406 inches Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches Hole Quantity:
Thread Direction: Right-hand Thread Length: 0.406 inches Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Right-hand Thread Length: 0.406 inches Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Thread Length: 0.406 inches Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
0.406 inches Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Fastener Length: 4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
4.781 inches Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Head Style: Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Hexagon Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Head Height: Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Hole Diameter: 0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
0.046 inches Thread Diameter: 0.190 inches Grip Length: 4.375 inches
Thread Diameter: 0.190 inches Grip Length: 4.375 inches
0.190 inches Grip Length: 4.375 inches
Grip Length: 4.375 inches
4.375 inches
Hole Quantity:
note quantity.
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140
Material Specification:
Mil-b-6812 military specification all material responses
Surface Treatment:
Cadmium

Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

NSN 5306-00-582-8796

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-b-6812 spec.