NSN 5306-00-582-9020



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-582-9020 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.782 inches **Fastener Length:** 0.844 inches **Head Style:** Hexagon **Head Height:** Between 0.265 inches and 0.297 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Hole Diameter:**

0.070 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

0.062 inches

Hole Quantity:

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.671 inches first hole

Material:

Stainless steel

Material Specification:

Qq-s-770 federal specification single material response

NSN 5306-00-582-9020

Machine Bolt - Page 2 of 2



Surface	Treatment:
---------	------------

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0