## NSN 5306-00-582-9889



6-00-582-9889

| Machine Bolt - Page 1 of 1                              |
|---|
| View Online at https://aerobasegroup.com/nsn/5306-00-   |
| Thread Class:   |
| 3a  |
| Thread Direction:                                       |
| Right-hand  |
| Thread Length:  |
| 0.406 inches  |
| Fastener Length:  |
| 5.031 inches  |
| Head Style:   |
| Hexagon   |
| Head Height:  |
| Between 0.109 inches and 0.141 inches                   |
| Width Between Flats:                                    |
| Between 0.365 inches and 0.377 inches                   |
| Thread Diameter:  |
| 0.190 inches  |
| Grip Length:  |
| 4.625 inches  |
| Features Provided:                                      |
| Finished head   |
| Thready Qty Per Inch (tpi):                             |
| 32  |
| Min. Tensile Strength (psi):                            |
| 125000 pounds per square inch                           |
| Hardness Rating:  |
| 26.0 rockwell c and 32.0 rockwell c                     |
| Material:   |
| Stainless steel   |
| Material Specification:                                 |
| Qq-s-770 federal specification single material response |
| Surface Treatment:                                      |
| Passivate   |
| Thread Series Designator:                               |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:                                       |
| No  |
| Fiig:   |
| A003b0  |
|   |