NSN 5306-00-584-4595

Machine Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-584-4595 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.499 inches and 0.530 inches |
| Fastener Length: |
| Between 3.890 inches and 3.937 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.203 inches and 0.234 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 3.359 inches and 3.391 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military |
| specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single |
| material response or mil-s-8695 military specification single material response |
| Surface Treatment: |

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

NSN 5306-00-584-4595

Machine Bolt - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-s-5626 spec.