## NSN 5306-00-584-4876

Machine Bolt - Page 1 of 2

**Thread Class:** 

Silver

View Online at https://aerobasegroup.com/nsn/5306-00-584-4876



3a **Thread Direction: Right-hand Thread Length:** Between 0.600 inches and 0.640 inches Fastener Length: Between 0.600 inches and 0.640 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.300 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.314 inches **Extended Washer Diameter:** Between 0.420 inches and 0.460 inches **Extended Washer Thickness:** Between 0.040 inches and 0.060 inches Hole Diameter: 0.062 inches **Thread Diameter:** 0.250 inches Hole Quantity: 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hardness Rating: 42.0 rockwell c and 43.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel **Material Specification:** C50t22 fscm 24446 mfr ref single material response **Surface Treatment:** 

## NSN 5306-00-584-4876

Machine Bolt - Page 2 of 2



Surface Treatment Specification:

Ams 2412 assn standard single treatment response

## **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0