

View Online at <https://aerobasegroup.com/nsn/5306-00-584-4923>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.611 inches and 0.687 inches

Fastener Length:

Between 3.438 inches and 3.484 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 2.797 inches and 2.827 inches

Hole Quantity:

1

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.250 inches first hole

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.