NSN 5306-00-584-4934

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-584-4934

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.640 inches Fastener Length: 0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter: 0.070 inches first hole
Thread Direction: Right-hand Thread Length: 0.640 inches Fastener Length: 0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Right-hand Thread Length: 0.640 inches Fastener Length: 0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Thread Length: 0.640 inches Fastener Length: 0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
0.640 inches Fastener Length: 0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Fastener Length:0.828 inchesHead Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:0.070 inchesShank Unthreaded Hole Diameter:
0.828 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
Hole Diameter: 0.070 inches Shank Unthreaded Hole Diameter:
0.070 inches Shank Unthreaded Hole Diameter:
Shank Unthreaded Hole Diameter:
0.070 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
0.188 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Stainless steel
Material Specification:
Qq-s-770 federal specification single material response
Surface Treatment:
Passivate

NSN 5306-00-584-4934

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

