NSN 5306-00-584-5142

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-584-5142 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.475 inches and 0.525 inches **Fastener Length:** Between 2.485 inches and 2.515 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.428 inches and 0.438 inches **Head Height:** 0.250 inches **Hole Diameter:** 0.037 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Round Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:**

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

NSN 5306-00-584-5142

Internal Wrenching Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-5626 spec.