NSN 5306-00-584-5503

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-584-5503 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.641 inches **Fastener Length:** 1.953 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches **Hole Diameter:** 0.070 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** 1.312 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats Distance From Head Largest Bearing Surface To Shank Hole Center: 1.750 inches first hole Material: Stainless steel

Material Specification:

Qq-s-770 federal specification single material response

NSN 5306-00-584-5503

Machine Bolt - Page 2 of 2



Surrace	ı reatment
Passivate	9

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0