NSN 5306-00-584-6735

Internal Wrenching Bolt - Page 1 of 1





3a Thread Direction: Right-hand Thread Length: Between 0.787 inches and 0.837 inches Fastener Length: Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Right-hand Thread Length: Between 0.787 inches and 0.837 inches Fastener Length: Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Thread Length: Between 0.787 inches and 0.837 inches Fastener Length: Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Between 0.787 inches and 0.837 inches Fastener Length: Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Fastener Length: Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Between 3.547 inches and 3.577 inches Head Style: Bevel-conical Head Diameter:
Head Style: Bevel-conical Head Diameter:
Bevel-conical Head Diameter:
Head Diameter:
Between 0.818 inches and 0.828 inches
Head Height:
0.500 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.376 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 40.0 rockwell c
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A003b0