

View Online at <https://aerobasegroup.com/nsn/5306-00-584-7362>

Thread Direction:

Right-hand

Thread Length:

Between 0.884 inches and 0.924 inches

Fastener Length:

Between 1.552 inches and 1.572 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

First Diameter From Head:

Between 0.276 inches and 0.286 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.628 inches and 0.688 inches

Thread Diameter:

0.312 inches

Nonstandard Thread Pitch Diameter:

+0.2797/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 30.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0