
NSN 5306-00-584-7898

Machine Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** Between 0.625 inches and 0.703 inches Fastener Length: Between 1.078 inches and 1.125 inches Head Style: Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.615 inches and 0.627 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.438 inches Grip Length: Between 0.422 inches and 0.453 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response Surface Treatment: Passivate **Thread Series Designator:**

Unf

NSN 5306-00-584-7898

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.

