

View Online at <https://aerobasegroup.com/nsn/5306-00-586-7841>

**Fastener Length:**

1.190 inches

**Eye Inside Diameter:**

Between 0.375 inches and 0.378 inches

**Shoulder Thickness:**

0.094 inches

**Shank Length:**

1.190 inches

**Eye Stock Thickness:**

Between 0.183 inches and 0.193 inches

**Shoulder Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.371 inches and 0.374 inches

**Overall Length:**

2.159 inches

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Center Of Eye To Shank End:**

1.784 inches

**Eye Outside Width:**

0.750 inches

**Special Features:**

Drilled hole 0.106 in. Diameter 1.070 in. From bearing surface of eye

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.