## NSN 5306-00-589-6570

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-589-6570

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.317 inches   |
| Fastener Length:   |
| Between 1.946 inches and 1.993 inches                            |
| Head Style:  |
| Double hexagon   |
| Head Height:   |
| Between 0.200 inches and 0.220 inches                            |
| Width Between Flats:   |
| Between 0.553 inches and 0.564 inches                            |
| Grip Diameter:   |
| Between 0.3740 inches and 0.3750 inches                          |
| Shank Unthreaded Hole Diameter:                                  |
| 0.106 inches first hole and 0.111 inches first hole              |
| Thread Diameter:   |
| 0.375 inches   |
| Grip Length:   |
| Between 0.1546 inches and 0.1593 inches                          |
| Thready Qty Per Inch (tpi):                                      |
| 24   |
| Criticality Code Justification:                                  |
| Anee   |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.831 inches first hole and 1.868 inches first hole              |
| Material:  |
| Steel  |
| Material Specification:  |
| 76301-23-105 mfr ref single material response                    |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                 |
| 76301 mfr ref single treatment response                          |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

---

## NSN 5306-00-589-6570

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

