

View Online at <https://aerobasegroup.com/nsn/5306-00-592-0675>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

2.829 inches

**Fastener Length:**

2.900 inches

**Head Style:**

Hexagon

**Head Height:**

0.160 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Hole Diameter:**

0.046 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.740 inches first hole

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.