## NSN 5306-00-593-1551

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-593-1551 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.235 inches **Fastener Length:** Between 0.440 inches and 0.450 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Hole Diameter:** 0.081 inches First Diameter From Head: Between 0.187 inches and 0.197 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.090 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** Material: Aluminum **Material Specification:** Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 2 military specification single treatment response

**Thread Series Designator:** 

Unf

## NSN 5306-00-593-1551

Externally Relieved Body Bolt - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
|                   |
| Fiig:             |

Mil-std (military Standard):

Mil-a-8625 spec.