NSN 5306-00-607-1142

Shear Bolt - Page 1 of 2



| Sileal Boil - Page 1 01 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5306-00-607-1142 | |
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.535 inches and 0.585 inches | |
| Fastener Length: | |
| Between 2.045 inches and 2.075 inches | |
| Head Style: | |
| Double hexagon w/hole | |
| Head Height: | |
| Between 0.388 inches and 0.398 inches | |
| Width Between Flats: | |
| Between 0.430 inches and 0.439 inches | |
| Extended Washer Diameter: | |
| Between 0.644 inches and 0.646 inches | |
| Extended Washer Thickness: | |
| Between 0.091 inches and 0.101 inches | |
| Grip Diameter: | |
| Between 0.3735 inches and 0.3745 inches | |
| Thread Diameter: | |
| 0.375 inches | |
| Grip Length: | |
| Between 1.490 inches and 1.510 inches | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Min. Tensile Strength (psi): | |
| 220000 pounds per square inch | |
| Hardness Rating: | |
| 46.0 rockwell c and 50.0 rockwell c | |
| Surface Finish: | |
| 32.0 microinches grip | |
| Product Name: | |
| Navy special project Material: | |
| | |
| Steel comp h11 | |
| Material Specification: | |

Ams 6487 assn standard single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074 cl 2 gr a military specification single treatment response

NSN 5306-00-607-1142

Shear Bolt - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| Mil-std (military Standard): |

Mil-c-26074 spec.