

View Online at <https://aerobasegroup.com/nsn/5306-00-607-1142>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.535 inches and 0.585 inches

**Fastener Length:**

Between 2.045 inches and 2.075 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.388 inches and 0.398 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.644 inches and 0.646 inches

**Extended Washer Thickness:**

Between 0.091 inches and 0.101 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074 cl 2 gr a military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-26074 spec.