

View Online at <https://aerobasegroup.com/nsn/5306-00-612-4686>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

Between 7.257 inches and 7.267 inches

Head Style:

Hexagon

Head Height:

0.250 inches

Width Between Flats:

Between 1.490 inches and 1.503 inches

Shoulder Diameter:

0.9975 inches first shoulder and 0.9985 inches first shoulder

Shoulder Length:

6.476 inches first shoulder and 6.486 inches first shoulder

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

7.101 inches first hole and 7.111 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Chromium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.