## NSN 5306-00-613-9035

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-613-9035

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.663 inches and 0.713 inches
Fastener Length:
Between 2.110 inches and 2.140 inches
Head Style:
Bevel-conical
Head Diameter:
Between 0.615 inches and 0.625 inches
Head Height:
0.343 inches
Hole Diameter:
0.070 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.375 inches and 0.378 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 3140 or steel comp 3135
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 3 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
20005 and 40 and an invalid advantal and advantal and

80205-nas146 professional/industrial association standard

## NSN 5306-00-613-9035

Internal Wrenching Bolt - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0