

View Online at <https://aerobasegroup.com/nsn/5306-00-614-6525>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.610 inches

**Fastener Length:**

1.490 inches

**Head Style:**

Dee

**Head Diameter:**

0.625 inches

**Head Height:**

0.195 inches

**Distance From Centerline To Flat:**

0.242 inches

**First Diameter From Head:**

Between 0.3952 inches and 0.3956 inches

**Second Diameter From Head:**

0.343 inches

**Third Diameter From Head:**

Between 0.3952 inches and 0.3956 inches

**Fourth Diameter From Head:**

0.300 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.360 inches and 0.470 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.415 inches and 0.535 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.800 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

0.880 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Steel comp 8740

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0