## NSN 5306-00-616-1534

Machine Bolt - Page 1 of 2



#### **Thread Class:**

1a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.750 inches and 0.810 inches

#### Fastener Length:

0.875 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.330 inches

#### Width Between Flats:

Between 0.304 inches and 0.313 inches

#### **Extended Washer Diameter:**

0.438 inches

#### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

#### Thread Diameter:

0.250 inches

## Grip Length:

Between 0.065 inches and 0.125 inches

## **Features Provided:**

Finished head

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

130000 pounds per square inch

#### Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

#### Minimum Yield Strength:

85000 pounds per square inch

#### Surface Finish:

63.0 microinches grip

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5732 assn standard single material response

## **Thread Series Designator:**

Unf

## Shelf Life:

N/a



# NSN 5306-00-616-1534

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

