## **NSN 5306-00-616-2622** Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-616-2622
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.407 inches
Fastener Length:
3.719 inches
Head Style:
Hexagon
Head Height:
0.156 inches
Width Between Flats:
0.500 inches
Grip Diameter:
0.3117 inches
Single Shear Strength:
7300 pounds per square inch
Thread Diameter:
0.312 inches
Grip Length:
3.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response or mil-s-8695 military specification 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:

N/a

## NSN 5306-00-616-2622

Shear Bolt - Page 2 of 2



--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.